




# wave panther



The **Wave Panther** takes over from the long running and successful Wave SE as our **premier wave sail**. Compared to the SE, the Panther has a **shorter boom** and is **lighter weight**. On the water, the Wave Panther has a smooth and direct power delivery, combined with very easy handling. The Panther's design advantage allows operation in a **wider wind range**, so you can sail longer without the need to re-rig.

The leech area of the Panther utilizes our new, low stretch **Technora-fiber sailcloth**, which delivers superior performance with less weight. The Panther's mid and luff sections are made of our **Spectra X film**, for strength

and **great visibility** throughout the body of the sail. We use higher density Spectra X film in the foot area to resist harness hook tears and nose-of-the-board punctures.

**Other key features include:** a removable down-haul pulley, weft reinforced sleeve cloth, flip-up adjustable mast pad, RBS battens and a vinyl window that won't scratch. Plus, **we rig every Wave Panther** before it is shipped so that you are ready to go with the correct batten tension and adjustable head setting.

At Ezzy, we constantly strive for the highest standards in our designs, materials, manufacturing and the **Wave Panther** carries on that tradition.

size	Luff		Boom		Suggested Mast		Ezzy Mast Base/Top	No. of Battens	Weight (Kg.)
	min	max	min	max	1st Choice	2nd. Choice			
2.9	318	319	127	131	340/28/15	370/27/17	340 / 340	5	2.71
3.3	339	340	136	141	340/28/15	370/27/17	340 / 340	5	2.89
3.5	353	354	142	146	340/28/15	370/27/17	340 / 340	5	3.01
3.7	361	362	147	151	370/27/17	340/28/15	340 / 370	5	3.10
4.0	373	374	150	155	370/27/17	400/25/19	370 / 370	5	3.15
4.2	382	383	154	158	370/27/17	400/25/19	370 / 370	5	3.25
4.5	394	395	156	161	370/27/17	400/25/19	370 / 400	5	3.36
4.7	405	406	161	166	400/25/19	430/25/21	400 / 400	5	3.46
5.0	418	419	166	171	400/25/19	430/25/21	400 / 400	5	3.56
5.2	431	432	170	174	430/25/21	400/25/21	400 / 430	5	3.68
5.5	436	437	171	177	430/25/21	460/25/25	430 / 430	5	3.75
5.8	444	446	175	181	430/25/21	460/25/25	430 / 430	5	3.85
6.0	452	454	179	185	430/25/21	460/25/25	430 / 430	5	3.97
6.3	455	457	185	190	430/25/21	460/25/25	430 / 430	5	4.05
6.9	485	487	186	193	460/25/25	460/25/25	460 / 460	5	4.31

